

DESCRIPTION

#900R MTL+ RUST Primer is a water based, acrylic emulsion, rust inhibiting primer. This primer not only adheres to difficult metallic substrates, but also gives good corrosion resistance over carbon steel. **#900R's** creative formulating makes it a very versatile water-based rust inhibiting primer. **#900R** water based rust inhibiting primer is formulated with a unique polymer that is designed to react with lightly rusted steel to form a bond and provide anticorrosion protection. **#900R MTL+ RUST Primer** can be over-coated with all Western Colloid topcoats and coatings.

PHYSICAL PROPERTIES

Color Yellow when cured
Consistency Light - Roll, Brush or Spray
Appearance.....Medium Bodied Liquid
Application Rate 1 gal. Per 200 sq. ft.
Application Temperature Minimum 50° F
Dry Time (through dehydration).....2 hr. @ 75° F
Cure Time6 hr. @ 75° F

PREPARATION

Remove all heavy rust scale by blasting or abrasive wheel. Light to moderate loose rust should be removed by wire brushing. Surface must be dry and free of dirt, dust, oil, grease, wax, rust, chalky or loose paint, mildew and any other surface contamination that may inhibit adhesion. New and galvanized steel should be cleaned to remove any surface deposits and sheen.

APPLICATION

Using roller, brush or spray equipment, apply to the properly prepared surface at the rate of 1 gallon per 200 sq. ft. over smooth or metal surfaces. **#900R MTL+ RUST Primer** should be allowed to completely cure before the application of the top coating.

Wet material and all tools and equipment may be cleaned with water. Rinse tools and equipment with water before using. Mix thoroughly before using. Do not dilute.

PRECAUTIONS: Do not apply **#900R MTL+ RUST Primer** when surface or air temperature is below 50° F, or if cold weather, rain or fog is expected within forty-eight hours of application. **#900R MTL+ RUST Primer** cures through dehydration. Drying time may vary depending upon wet film thickness, temperature, humidity and air movement. Do not leave **#900R MTL+ RUST Primer** in spray hose when not in use. Flush hoses with fresh water.

READ AND FOLLOW DIRECTIONS CAREFULLY. REFER TO MSDS FOR PROPER HANDLING.
STORE CONTAINERS IN COOL, DRY, PROTECTED AREA. KEEP FROM FREEZING

LIMITED WARRANTY

WESTERN COLLOID warrants its products to be of merchantable quality and suitable for the general purpose for which they were intended, when applied in accordance with WESTERN COLLOID's instructions. WESTERN COLLOID does not warrant its products to be suitable for any purpose or use other than for which they were intended. Liability under this warranty is limited to supplying new material without charge, or at WESTERN COLLOID's option, to a refund of the purchase price. In the event of a claim under this warranty, notice must be given in writing at the addresses shown here on. THIS LIMITED WARRANTY IS ISSUED AND ACCEPTED IN LIEU OF ALL OTHER EXPRESSED WARRANTIES, AND EXPRESSLY EXCLUDES LIABILITY FOR CONSEQUENTIAL DAMAGES. SOME STATES DO NOT ALLOW THE EXCLUSION OR LIMITATION OF INCIDENTAL OR CONSEQUENTIAL DAMAGES OR LIMITATION ON HOW LONG AN IMPLIED WARRANTY LASTS, SO THE ABOVE LIMITATIONS AND EXCLUSIONS MAY NOT APPLY TO YOU.

TEC900R 1508A