

## DESCRIPTION

**Western Colloid #8000 All Weather Elastic Cement** is a unique, solvent-based, white sealant. **#8000** is designed for use on various roof membranes and surfaces, including asphalt BUR, modified bitumen, metal and single ply roofs. (Including EPDM, PVC, TPO and Hypalon). It is formulated with extremely tough elastomers resins and binders, to form a long lasting seal that will outperform asphalt based sealants. **#8000** has excellent elongation and flexibility and it contains synthetic fibers giving it the strength and toughness to perform in all climates. **#8000** has special additives which allow it to be applied to wet or underwater surfaces. It has excellent sag resistance which allows it to be applied to vertical as well as horizontal surfaces. **#8000** is waterproof immediately upon application and can be used before or during wet weather.

## PHYSICAL PROPERTIES

Color.....	White
Volume Solids .....	50%
Consistency.....	Heavy, for Trowel or Stiff Brush
Elongation .....	300%
Flash Point.....	> 100° F
Weatherability .....	Excellent
Application Rate.....	1/8 in. thick = 1 gal. per 12 sq. ft.
VOC .....	< 300g/l

## PREPARATION

Surface must be clean, sound and free of grease, wax, chalky or loose paint, mildew and any other surface contamination that may inhibit adhesion.

## APPLICATION

Using a trowel or stiff brush apply to the surface at a thickness of 1/8 inch. **#8000** may be reinforced with polyester fabric in a "3 course" method for added strength or to bridge voids or gaps. When applying to wet surfaces, use sufficient pressure to displace the moisture and insure proper adhesion. Before top coating with a water-based product, allow to dry at least 48 hours.

Clean up with mineral spirits. Do not thin or dilute.

**CAUTION:** Combustible mixture, keep away from heat and open flames. Avoid prolonged contact with or inhalation of solvent fumes. A NIOSH approved respirator with organic vapor cartridge is recommended. Do not take internally. If swallowed do not induce vomiting. Contact medical personnel immediately. For professional use only.

READ AND FOLLOW DIRECTIONS CAREFULLY. REFER TO MSDS FOR PROPER HANDLING.  
STORE CONTAINERS IN COOL, DRY, PROTECTED AREA.

---

### LIMITED WARRANTY

WESTERN COLLOID warrants its products to be of merchantable quality and suitable for the general purpose for which they were intended, when applied in accordance with WESTERN COLLOID's instructions. WESTERN COLLOID does not warrant its products to be suitable for any purpose or use other than for which they were intended. Liability under this warranty is limited to supplying new material without charge, or at WESTERN COLLOID's option, to a refund of the purchase price. In the event of a claim under this warranty, notice must be given in writing at the addresses shown hereon. THIS LIMITED WARRANTY IS ISSUED AND ACCEPTED IN LIEU OF ALL OTHER EXPRESSED WARRANTIES, AND EXPRESSLY EXCLUDES LIABILITY FOR CONSEQUENTIAL DAMAGES. SOME STATES DO NOT ALLOW THE EXCLUSION OR LIMITATION OF INCIDENTAL OR CONSEQUENTIAL DAMAGES OR LIMITATION ON HOW LONG AN IMPLIED WARRANTY LASTS, SO THE ABOVE LIMITATIONS AND EXCLUSIONS MAY NOT APPLY TO YOU.

---