



PRODUCT #9000 ROOF WASH & PRIME

FLUID APPLIED ROOFING SYSTEMS

REFLECTIVE COATINGS

ASPHALT SEALCOATS

DESCRIPTION

Western Colloid #9000 Roof Wash & Prime is a low viscosity detergent intended for application to all types of roof surfaces prior to power washing. **#9000** lifts dirt and grease from the surface of the roof. **#9000** is formulated from surfactants and alkaline cleaning agents. **#9000** also aids in the adhesion of acrylic coatings to oxidized surfaces. It is designed for use on asphalt, modified bitumen, metal an single ply roofs. (Including TPO, PVC, Hypalon and EPDM). It is especially important to clean EPDM with #9000 prior to coating with ElastaHyde acrylic coating.

PHYSICAL PROPERTIES

Solids	5% min.
Weight per gallon	9.3 lbs.
Application Rate 300-400 sq.ft per ga	I. (diluted)
Application As necessary to allow 15 mi	in. wet time
Flash Point	None

APPLICATION

Mix one part **#9000** with four parts water. Over or under dilution will affect performance. Apply with a garden type sprayer in sufficient quantity so as to wet out the surface for a minimum of 15 minutes without drying. The primer should then be thoroughly power washed from the roof, a final clean water rinse is recommended. Although all efforts have been made to reduce the effect, this product will cause the roof surface to become more slippery. All necessary precautions should be taken by the applicator to avoid injury.

PRECAUTIONS: Avoid prolonged contact with skin or fumes. This is a highly alkaline material. Wear appropriate protective clothing including rubber gloves and safety goggles. If irritation occurs, flush with water and seek medical attention. If swallowed, do not induce vomiting. Keep out of reach of children.

WARNING: This product contains a chemical known to the State of California to cause cancer.

READ AND FOLLOW DIRECTIONS CAREFULLY. REFER TO MSDS FOR PROPER HANDLING. NOT DOT REGULATED. STORE CONTAINERS IN COOL, DRY, PROTECTED AREA. KEEP FROM FREEZING

LIMITED WARRANTY

WESTERN COLLOID warrants its products to be of merchantable quality and suitable for the general purpose for which they were intended, when applied in accordance with WESTERN COLLOID's instructions. WESTERN COLLOID does not warrant its products to be suitable for any purpose or use other than for which they were intended. Liability under this warranty is limited to supplying new material without charge, or at WESTERN COLLOID's option, to a refund of the purchase price. In the event of a claim under this warranty, notice must be given in writing at the addresses shown here on. THIS LIMITED WARRANTY IS ISSUED AND ACCEPTED IN LIEU OF ALL OTHER EXPRESSED WARRANTIES, AND EXPRESSLY EXCLUDES LIABILITY FOR CONSEQUENTIAL DAMAGES. SOME STATES DO NOT ALLOW THE EXCLUSION OR LIMITATION OF INCIDENTAL OR CONSEQUENTIAL DAMAGES OR LIMITATION ON HOW LONG AN IMPLIED WARRANTY LASTS, SO THE ABOVE LIMITATIONS AND EXCLUSIONS MAY NOT APPLY TO YOU.

TEC9000 1508a