

DESCRIPTION

Product No. 930 TPO Primer is a water based, clear, acrylic primer. It is formulated with a unique, premium acrylic resin that is designed to enhance the adhesion of acrylic coatings to aged TPO single ply membranes. **#930 TPO Primer** eliminates the need of a special base coat that is required when applying acrylic coatings to TPO membranes. Not for use over EPDM, PVC or other single ply membranes.

PHYSICAL PROPERTIES

Color..... Clear when dry
Total Solids..... 31% by weight
Consistency..... Light, Roll, Brush or Spray
Appearance..... Wet – Milky Liquid
Application Rate..... ½ gal. per 100 sq. ft.
Application Temperature..... Minimum 50° F
Dry Time (through dehydration)..... 2 hr. @ 75° F
Cure Time..... 12 hr. @ 75° F
Tack free time..... 30 Min.

PREPARATION

Surface must be dry and free of dirt, dust, oil, grease, wax, rust, chalky or loose paint, mildew and any other surface contamination that may inhibit adhesion. Washing surface is recommended prior to application.

APPLICATION

Using roller, brush or spray equipment, apply to the properly prepared surface at the rate of ½ gallon per 100 sq. ft. over smooth TPO surfaces. **#930 TPO Primer** should be allowed to completely cure before the application of the top coating.

Wet material and all tools and equipment may be cleaned with water. Rinse tools and equipment with water before using. Mix thoroughly before using. Do not dilute.

PRECAUTIONS: Do not apply **#930 TPO Primer** when surface or air temperature is below 50° F, or if cold weather, rain or fog is expected within forty-eight hours of application. **#930 TPO Primer** cures through dehydration. Drying time may vary depending upon wet film thickness, temperature, humidity and air movement.

READ AND FOLLOW DIRECTIONS CAREFULLY. REFER TO MSDS FOR PROPER HANDLING. NOT DOT REGULATED.

STORE CONTAINERS IN COOL, DRY, PROTECTED AREA. KEEP LIDS TIGHTLY CLOSED KEEP FROM FREEZING

LIMITED WARRANTY

WESTERN COLLOID warrants its products to be of merchantable quality and suitable for the general purpose for which they were intended, when applied in accordance with WESTERN COLLOID's instructions. WESTERN COLLOID does not warrant its products to be suitable for any purpose or use other than for which they were intended. Liability under this warranty is limited to supplying new material without charge, or at WESTERN COLLOID's option, to a refund of the purchase price. In the event of a claim under this warranty, notice must be given in writing at the addresses shown hereon. THIS LIMITED WARRANTY IS ISSUED AND ACCEPTED IN LIEU OF ALL OTHER EXPRESSED WARRANTIES, AND EXPRESSLY EXCLUDES LIABILITY FOR CONSEQUENTIAL DAMAGES. SOME STATES DO NOT ALLOW THE EXCLUSION OR LIMITATION OF INCIDENTAL OR CONSEQUENTIAL DAMAGES OR LIMITATION ON HOW LONG AN IMPLIED WARRANTY LASTS, SO THE ABOVE LIMITATIONS AND EXCLUSIONS MAY NOT APPLY TO YOU.
