



FLUID APPLIED ROOFING SYSTEMS

REFLECTIVE COATINGS - ASPHALT

STITCHBONDED POLYESTER FABRICS

WCP-SF	Standard - Firm Finish	Products: Western Colloid (W-26) or TieTex (T-326)
	Description:	2.75-3oz. Standard-weight Stitchbonded Polyester Fabric with a firm finish. WCP-SF has good strength and elongation. WCP-SF has good conformability on smooth or semi-smooth surfaces. WCP-SF works well when used <u>over smooth or cap sheet surfaces</u> . It has fewer stitches per inch which allows for better wetability which requires less brooming. Because it has a firm (starched) finish it will have fewer wrinkles and will lay straighter during application. This will speed up application time giving greater production.
	Sizes:	40 inches x 324 feet = 10 squares (1080 sq.ft.)

WCP-SS	Standard - Soft Finish	Products: TieTex (T-325) or Equal
	Description:	2.75-3oz. Standard-weight Stitchbonded Polyester Fabric with a soft finish. WCP-SS has good strength and elongation. WCP-SS has excellent conformability on semi-smooth or rough surfaces. WCP-SS works well when used <u>over vacuumed, spudded or filled gravel</u> <u>surfaces</u> . It has fewer stitches per inch which allows for better wetability which requires less brooming.
	Sizes:	40 inches x 324 feet = 10 squares (1080 sq.ft.)

WCP-HS	Heavy - Soft Finish	Products: TieTex (T-272) or Equal
	Description:	3oz. Heavy-weight Stitchbonded Polyester Fabric with a medium soft finish. WCP-HS has excellent strength and elongation. WCP-HS has good conformability on smooth or semi-smooth surfaces. This product works well when used over cap sheet, smooth and spudded or filled gravel roofs. WCP-HS has more and closer stitches which may require extra brooming to insure proper embeddment and removal of all air pockets. WCP-HS also comes in cut width rolls which are excellent for flashing, seams, walls and metal roofs.
	Sizes:	40 inches x 324 feet = 10 squares (1080 sq.ft.) 4 inches x 300 feet 6 inches x 300 feet 12 inches x 300 feet 20 inches x 300 feet