



# PRODUCT #925 CLEAR SKYLIGHT COATING

**FLUID APPLIED ROOFING SYSTEMS** 

**REFLECTIVE COATINGS** 

**ASPHALT SEALCOATS** 

#### **DESCRIPTION**

**Product No. 925 Clear Skylight Coating** is a water based, clear, acrylic coating. It is formulated with premium acrylic resin, to form a hard, long lasting, clear surface on aged and worn <u>fiberglass</u> skylights. When applied properly it will give worn <u>fiberglass</u> skylights additional years of useful life. **Clear Skylight Coating** may also be used as a clear sealer on other surfaces such as wood and masonry.

## **PHYSICAL PROPERTIES**

Color	Clear when dry
Total Solids	45-55% by weight
Consistency	. Light, Roll, Brush or Spray
Appearance	Wet – Milky Liquid
	Excellent
Application Rate	1 - 3 Gal. per 100 sq. ft.
Application Temperature.	Minimum 60° F
	ration)1 hr. @ 75° F

#### **PREPARATION**

Surface must be dry and free of dirt, dust, oil, grease, wax, rust, chalky or loose paint, mildew and any other surface contamination that may inhibit adhesion. Repair any splits or holes using proper sealing compound.

#### **APPLICATION**

Using roller, brush or spray equipment, apply to the properly prepared surface at the rate of 1 to 3 gallons per 100 sq. ft.. Severely weathered skylights with exposed fiberglass strands may require two or more additional coats. Wait 30 minutes to 1 hour between coats.

Wet material and all tools and equipment may be cleaned with water. Rinse tools and equipment with water before using. Mix thoroughly before using. Do not dilute.

**PRECAUTIONS:** Do not apply **Clear Skylight Coating** when surface or air temperature is below 60° F, or if cold weather, rain or fog is expected within twenty-four hours of application. **Clear Skylight Coating** cures through dehydration. Drying time may vary depending upon wet film thickness, temperature, humidity and air movement. Not intended for use on Acrylic or Plexiglass skylights.

READ AND FOLLOW DIRECTIONS CAREFULLY. REFER TO MSDS FOR PROPER HANDLING. NOT DOT REGULATED STORE CONTAINERS IN COOL, DRY, PROTECTED AREA. KEEP FROM FREEZING

## LIMITED WARRANTY

WESTERN COLLOID warrants its products to be of merchantable quality and suitable for the general purpose for which they were intended, when applied in accordance with WESTERN COLLOID's instructions. WESTERN COLLOID does not warrant its products to be suitable for any purpose or use other than for which they were intended. Liability under this warranty is limited to supplying new material without charge, or at WESTERN COLLOID's option, to a refund of the purchase price. In the event of a claim under this warranty, notice must be given in writing at the addresses shown hereon. THIS LIMITED WARRANTY IS ISSUED AND ACCEPTED IN LIEU OF ALL OTHER EXPRESSED WARRANTIES, AND EXPRESSLY EXCLUDES LIABILITY FOR CONSEQUENTIAL DAMAGES. SOME STATES DO NOT ALLOW THE EXCLUSION OR LIMITATION OF INCIDENTAL OR CONSEQUENTIAL DAMAGES OR LIMITATION ON HOW LONG AN IMPLIED WARRANTY LASTS, SO THE ABOVE LIMITATIONS AND EXCLUSIONS MAY NOT APPLY TO YOU.

TEC925 1105b