



Safety Data Sheet (SDS)

OSHA HazCom 2012 Standard 29 CFR 1910.1200. Prepared to GHS Rev03.

Printing date 06/13/2014

Reviewed on 06/13/2023

* 1 Identification

- **Product identifier**
- **Trade name:** #298E Elastomeric Asphalt Emulsion
- **Product description** Water based Asphaltic Roof Coating
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
Western Colloid S.C., Inc.
654 E. 60th Street
Los Angeles, CA 90001 USA
Phone: 1-800-464-8292
Fax: 1-323-231-7648
www.westerncolloid.com
- **Emergency telephone number:** 1-323-231-8292

* 2 Hazard(s) identification

- **Classification of the substance or mixture**



Health hazard

May cause cancer.



Causes skin irritation.

May cause respiratory irritation.

Causes eye irritation.

- **Label elements**

- **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

- **Hazard pictograms**



GHS07



GHS08

- **Signal word** Danger
- **Hazard-determining components of labeling:**

Asphalt

Quartz (SiO₂)

- **Hazard statements**

Causes skin and eye irritation.

May cause cancer.

May cause respiratory irritation.

- **Precautionary statements**

Avoid breathing dust/fume/gas/mist/vapors/spray.

Use only outdoors or in a well-ventilated area.

Wear protective gloves/protective clothing/eye protection/face protection.

(Contd. on page 2)

**Safety Data Sheet (SDS)**

OSHA HazCom 2012 Standard 29 CFR 1910.1200. Prepared to GHS Rev03.

Printing date 06/13/2014

Reviewed on 06/13/2023

Trade name: #298E Elastomeric Asphalt Emulsion

(Contd. of page 1)

Use personal protective equipment as required.

Wash thoroughly after handling.

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Specific treatment (see on this label).

Take off contaminated clothing and wash before reuse.

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

IF exposed or concerned: Get medical advice/attention.

If skin irritation occurs: Get medical advice/attention.

If eye irritation persists: Get medical advice/attention.

IF ON SKIN: Wash with plenty of water.

Call a POISON CENTER/doctor if you feel unwell.

Store locked up.

Store in a well-ventilated place. Keep container tightly closed.

Dispose of contents/container in accordance with local/regional/national/international regulations.

Classification system:**NFPA ratings (scale 0 - 4)**

Health = 1

Fire = 0

Reactivity = 0

HMIS-ratings (scale 0 - 4)

Health = 1

Fire = 0

Reactivity = 0

*** 3 Composition/information on ingredients**

25852-37-3	n-Butyl acrylate-methyl methacrylate copolymer	15-35%
7732-18-5	water, distilled, conductivity or of similar purity	25-50%

Chemical characterization: Mixtures**Description:** Mixture of the substances listed below with nonhazardous additions.**Dangerous components:**

8052-42-4	Asphalt	25-50%
	☠ Carc. 2, H351; ⚠ Skin Irrit. 2, H315; STOT SE 3, H335; Eye Irrit. 2B, H320	
14808-60-7	Quartz (SiO ₂)	<1.0%
	☠ Carc. 1A, H350; STOT RE 1, H372; ⚠ Acute Tox. 4, H332; STOT SE 3, H335; Eye Irrit. 2B, H320	

4 First-aid measures**Description of first aid measures****After inhalation:** In case of unconsciousness, place patient securely on side position for transportation.**After skin contact:** Immediately wash with water and soap and rinse thoroughly.**After eye contact:**

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

After swallowing: Give large amounts of water. If symptoms persist consult doctor.**Most important symptoms and effects, both acute and delayed** No further relevant information available.

(Contd. on page 3)



Safety Data Sheet (SDS)

OSHA HazCom 2012 Standard 29 CFR 1910.1200. Prepared to GHS Rev03.

Printing date 06/13/2014

Reviewed on 06/13/2023

Trade name: #298E Elastomeric Asphalt Emulsion

(Contd. of page 2)

· Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Fire-fighting measures

· Extinguishing media**· Suitable extinguishing agents:**CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.**· Special hazards arising from the substance or mixture** No further relevant information available.**· Advice for firefighters****· Protective equipment:** No special measures required.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures Not required.**· Environmental precautions:** Dilute with plenty of water.**· Methods and material for containment and cleaning up:**

Absorb with liquid-binding material (ie. sand, diatomite, acid binders, universal binders, sawdust).

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

· Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

· Information about protection against explosions and fires: No special measures required.**· Conditions for safe storage, including any incompatibilities****· Storage:****· Requirements to be met by storerooms and receptacles:** No special requirements.**· Information about storage in one common storage facility:** Not required.**· Further information about storage conditions:** Keep receptacle tightly sealed.**· Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

· Additional information about design of technical systems: No further data; see section 7.**· Control parameters****· Components with occupational exposure limits:****8052-42-4 Asphalt**REL Ceiling limit value: 5* mg/m³
15-min; See Pocket Guide App. ATLV Long-term value: 0.5 mg/m³
*inh. fraction; as benzene-soluble aerosol; BEIp**14808-60-7 Quartz (SiO₂)**

PEL see Quartz listing

(Contd. on page 4)

Safety Data Sheet (SDS)

OSHA HazCom 2012 Standard 29 CFR 1910.1200. Prepared to GHS Rev03.

Printing date 06/13/2014

Reviewed on 06/13/2023

Trade name: #298E Elastomeric Asphalt Emulsion

(Contd. of page 3)

REL	Long-term value: 0.05* mg/m ³ *respirable dust; See Pocket Guide App. A
TLV	Long-term value: 0.025* mg/m ³ *as respirable fraction
· Ingredients with biological limit values:	
8052-42-4 Asphalt	
BEI	- urine end of shift at end of workweek 1-Hydroxypyrene with hydrolysis (nonquantitative)

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing.
Wash hands before breaks and at the end of work.
Avoid contact with the eyes and skin.

· **Breathing equipment:** Not required.

· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Select glove material based on penetration times, rates of diffusion and degradation.

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break-through time has to be determined and observed by the manufacturer of the protective gloves.

· **Eye protection:** Tightly sealed goggles

* 9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

Form:

Viscous

Color:

Brown

· **Odor:**

Mild asphaltic

· **Odor threshold:**

Not determined.

· **pH-value:**

Not determined.

· **Change in condition**

Melting point/Melting range:

Not determined.

(Contd. on page 5)

**Safety Data Sheet (SDS)**

OSHA HazCom 2012 Standard 29 CFR 1910.1200. Prepared to GHS Rev03.

Printing date 06/13/2014

Reviewed on 06/13/2023

Trade name: #298E Elastomeric Asphalt Emulsion

(Contd. of page 4)

Boiling point/Boiling range:	100 °C (212 °F)
· Flash point:	Not applicable.
· Flammability (solid, gaseous):	Not applicable.
· Ignition temperature:	
Decomposition temperature:	Not determined.
· Auto igniting:	Product is not selfigniting.
· Danger of explosion:	Product does not present an explosion hazard.
· Explosion limits:	
Lower:	0.0 Vol %
Upper:	0.0 Vol %
· Vapor pressure @ 20 °C (68 °F):	23 hPa (17 mm Hg) 17 mmHg
· Density @ 20 °C (68 °F):	1.02 g/cm ³ (8.512 lbs/gal)
· Relative density	Not determined.
· Vapour density	Not determined.
· Evaporation rate	<1
· Solubility in / Miscibility with Water:	Fully miscible.
· Partition coefficient (n-octanol/water):	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Solvent content:	
Organic solvents:	0.0 %
Water:	45.2 %
VOC content:	8.8 %
Solids content:	46.0 %
· Other information	No further relevant information available.

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**
- **Primary irritant effect:**
- **on the skin:** Irritant to skin and mucous membranes.
- **on the eye:** Irritating effect.

(Contd. on page 6)



Safety Data Sheet (SDS)

OSHA HazCom 2012 Standard 29 CFR 1910.1200. Prepared to GHS Rev03.

Printing date 06/13/2014

Reviewed on 06/13/2023

Trade name: #298E Elastomeric Asphalt Emulsion

(Contd. of page 5)

- **Sensitization:** No sensitizing effects known.

- **Additional toxicological information:**

The product shows the following dangers according to internally approved calculation methods for preparations:

Irritant

- **Carcinogenic categories**

- **IARC (International Agency for Research on Cancer)**

8052-42-4	Asphalt	2B
14808-60-7	Quartz (SiO ₂)	1

- **NTP (National Toxicology Program)**

14808-60-7	Quartz (SiO ₂)	K
------------	----------------------------	---

- **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

12 Ecological information

- **Toxicity**

- **Aquatic toxicity:** No further relevant information available.

- **Persistence and degradability** No further relevant information available.

- **Bioaccumulative potential** No further relevant information available.

- **Mobility in soil** No further relevant information available.

- **Additional ecological information:**

- **General notes:** Generally not hazardous for water

- **Results of PBT and vPvB assessment**

- **PBT:** Not applicable.

- **vPvB:** Not applicable.

- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**

- **Recommendation:**

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- **Uncleaned packagings:**

- **Recommendation:** Disposal must be made according to official regulations.

- **Recommended cleansing agent:** Water, if necessary with cleansing agents.

14 Transport information

- **UN-Number**

- **DOT, ADR, ADN, IMDG, IATA** Non-Regulated Material

- **UN proper shipping name**

- **DOT, ADR, ADN, IMDG, IATA** Non-Regulated Material

- **Transport hazard class(es)**

- **DOT, ADR, ADN, IMDG, IATA**

- **Class** Non-Regulated Material

- **Packing group**

- **DOT, ADR, IMDG, IATA** Non-Regulated Material

- **Environmental hazards:**

- **Marine pollutant:** No

(Contd. on page 7)



Safety Data Sheet (SDS)

OSHA HazCom 2012 Standard 29 CFR 1910.1200. Prepared to GHS Rev03.

Printing date 06/13/2014

Reviewed on 06/13/2023

Trade name: #298E Elastomeric Asphalt Emulsion

(Contd. of page 6)

- **Special precautions for user** Not applicable.
- **Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code** Not applicable.
- **UN "Model Regulation":** -

*15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Sara**

- **Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

- **Section 313 (Specific toxic chemical listings):**

None of the ingredients is listed.

- **TSCA (Toxic Substances Control Act):**

All ingredients are listed.

- **Proposition 65**

- **Chemicals known to cause cancer:**

14808-60-7 Quartz (SiO₂)

- **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

- **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

- **Chemicals known to cause developmental toxicity:**

None of the ingredients is listed.

- **Carcinogenic categories**

- **EPA (Environmental Protection Agency)**

None of the ingredients is listed.

- **TLV (Threshold Limit Value established by ACGIH)**

8052-42-4	Asphalt	A4
14808-60-7	Quartz (SiO ₂)	A2

- **NIOSH-Ca (National Institute for Occupational Safety and Health)**

8052-42-4	Asphalt
14808-60-7	Quartz (SiO ₂)

- **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

- **Hazard pictograms**



GHS07 GHS08

- **Signal word** Danger

- **Hazard-determining components of labeling:**

Asphalt
Quartz (SiO₂)

(Contd. on page 8)

**Safety Data Sheet (SDS)**

OSHA HazCom 2012 Standard 29 CFR 1910.1200. Prepared to GHS Rev03.

Printing date 06/13/2014

Reviewed on 06/13/2023

Trade name: #298E Elastomeric Asphalt Emulsion

(Contd. of page 7)

· Hazard statements

Causes skin and eye irritation.
May cause cancer.
May cause respiratory irritation.

· Precautionary statements

Avoid breathing dust/fume/gas/mist/vapors/spray.
Use only outdoors or in a well-ventilated area.
Wear protective gloves/protective clothing/eye protection/face protection.
Use personal protective equipment as required.
Wash thoroughly after handling.
Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
Specific treatment (see on this label).
Take off contaminated clothing and wash before reuse.
IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
IF exposed or concerned: Get medical advice/attention.
If skin irritation occurs: Get medical advice/attention.
If eye irritation persists: Get medical advice/attention.
IF ON SKIN: Wash with plenty of water.
Call a POISON CENTER/doctor if you feel unwell.
Store locked up.
Store in a well-ventilated place. Keep container tightly closed.
Dispose of contents/container in accordance with local/regional/national/international regulations.

· National regulations:

The product is subject to be labeled according with the prevailing version of the regulations on hazardous substances.

· State Right to Know

8052-42-4	Asphalt	25-50%
	☠ Carc. 2, H351; ☠ Skin Irrit. 2, H315; STOT SE 3, H335; Eye Irrit. 2B, H320	
25852-37-3	n-Butyl acrylate-methyl methacrylate copolymer	15-35%
14808-60-7	Quartz (SiO ₂)	<1%
	☠ Carc. 1A, H350; STOT RE 1, H372; ☠ Acute Tox. 4, H332; STOT SE 3, H335; Eye Irrit. 2B, H320	
25265-77-4	2,2,4-Trimethyl-1,3-pentanediol monoisobutyrate	<1%
7732-18-5	water, distilled, conductivity or of similar purity	25-50%
All ingredients are listed.		

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Date of preparation / last revision** 06/13/2014 / 1

· Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
DOT: US Department of Transportation
IATA: International Air Transport Association
ACGIH: American Conference of Governmental Industrial Hygienists

(Contd. on page 9)



Safety Data Sheet (SDS)

OSHA HazCom 2012 Standard 29 CFR 1910.1200. Prepared to GHS Rev03.

Printing date 06/13/2014

Reviewed on 06/13/2023

Trade name: #298E Elastomeric Asphalt Emulsion

(Contd. of page 8)

EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
NFPA: National Fire Protection Association (USA)
HMIS: Hazardous Materials Identification System (USA)
VOC: Volatile Organic Compounds (USA, EU)
Acute Tox. 4: Acute toxicity, Hazard Category 4
Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2
Eye Irrit. 2B: Serious eye damage/eye irritation, Hazard Category 2B
Carc. 1A: Carcinogenicity, Hazard Category 1A
Carc. 2: Carcinogenicity, Hazard Category 2
STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3
STOT RE 1: Specific target organ toxicity - Repeated exposure, Hazard Category 1

· *** Data compared to the previous version altered.**

SDS / MSDS Created by MSDS Authoring Services (www.MSDSAuthoring.com)